



Modell	A mm	B mm	C mm	D mm	E mm	M	N mm	V mm	Vikt kg
CFA250-100	212	100	24	60	53	M100x4-6g	37	-	4.4
CFA250-200	312	100	24	60	53	M100x4-6g	37	-	5.9
CFA500-100	223.5	140	31	85	75	M140x4-6g	45	21	9.2
CFA500-200	323.5	140	31	85	75	M140x4-6g	45	21	12.7
CFA750-100	235.5	170	18	100	75	M170x4-6g	54	31	14.0
CFA750-200	335.5	170	18	100	75	M170x4-6g	54	31	18.3
CFA1000-100	243	190	39	110	95	M190x4-6g	56	34	18.4
CFA1000-200	343	190	39	110	95	M190x4-6g	56	34	24.7

Material	Anne. dimension	Värmebehandling	Ytbehandling
-	-	-	-
Tillåtna måttavvikelser där ej annat anges		Smältsvetsade konstr.	
Bärförskade del. enl. SS-ISO-2768-J		Gjutna del. enl. SS-EN ISO 13920	
Konstr.	Ritad	Datum	Produkt
	MN	04-Oct-06	CFA250/500/750/1000-100/200
Prod.godk.	Konstr.godk.	Skala	Benämning
061004	061004	3:10	
REHOBOT®			MÄTTRITNING
			B-47180