



CH 62; CHF 62

Description	Max working pressure, MPa	Capacity kN	Stroke mm	Pistonarea cm ²	Stroke vol. cm ³	A mm	B Ømm	C mm	D Ømm	E Ømm	G mm	H mm	J mm	K mm	L mm	M mm	N mm	Y mm	AA Ømm	AB mm	Weight kg
CH 62	70	61	50	8,8	44	110	55	22	30	29	M24x1,5	10	47	M6	9	M55x1,5	22	54	17	Ø17,2	1,6
CHF 62	70	61	50	8,8	44	136	55	22	30	29	M24x1,5	10	47	M6	9	M55x1,5	22	54	17	Ø17,2	2
CHF446,49	70	61	50	8,8	44	136	55	22	30	29	M24x1,5	10	47	M6	9	M55x1,5	22	54	17	M16	2

Material		Anse, dimension		Värmebehandling		Ytbehandling	
Tillägna måttavvikelse där ej annat anges				Smältavvikelse konstr.		Ytjämnhet	
Bearbetade del. Gjutna del.				ent.SS-ISO-2768-L		ent.SHS 723	
Konstr.	Ritad	Datum	Produkt	Tol-system		Rajon	
Prod.godk.	06-06-14	Skala	CH/CHF - CYLINDRAR	ent. ISO		E	
1:1				Benämning		Ersätter	
REHOBOT®				General dimension drawing		C-425,06; C-46109	
						Ersatt av	
						B-425,06	

Pos.	Ändring	Datum	Sign.
------	---------	-------	-------